



POLIFILM ITALIA S.R.L.
44020 SAN GIOVANNI DI OSTELLATO (FE) ITALIA

PRODUCT INFORMATION

PF 12/2/25 WPET TRANSP

Article number: 4034601

Description of the Product: Film backing: Polyester
Color: clear
Adhesive type: Acrylic, water based

Technical data: Thickness: 25 µm***
Adhesion to stainless steel : 125 +25/-25 cN/25mm / 0.5 +0.1/-0.1 N/cm
(AFERA 4001)*

Application: The **PF 12/2/25 WPET TRANSP** is recommended for the protection of sensitive surfaces against dirt and damage during processing. When applied correctly, the film can be removed without leaving any residues. As per our actual knowledge, the film is suitable for e.g. the following surfaces:

- HPL, smooth surfaces
- This article is suitable for thermoforming

Application conditions: - The surface must be free from oil, fat, dust and solvents
- Room temperature (> 10°C and < 40°C)

Resistance: - Against moisture: Moderate
- Against oil: Low
- Against solvents: Low
- Against UV: None

Storage conditions of rolls: - Room temperature (> 10°C and < 40°C)
- Storage time max. 6 months after date of production
- No direct exposure to sunlight and moisture

* Modified according to internal method for protective tapes

*** Internal method of measurement

Note:

The data and recommendations are given in good faith, on the basis of practical experience, but without warranty. The data stated above are average values of the production and are subject to tolerances of +/- 15%. The aforementioned characteristics are valid for standard surfaces. The film's performance may differ on specific surfaces, when applied under specific conditions. For this reason, it is highly recommended to the customer to carry out own tests under own specific conditions.

Technical modifications reserved.

All claims regarding liability and responsibility are based on the individual arrangements in the contract agreement, if not superseded by legal regulations.

Status: 01/12/2018 Rev. 21/01/2019